



CROSS SECTION 'A'

PLAN VIEW

ISOMETRIC VIEW

mm
[Inches]
ALL DIMENSIONS DEFAULT TO MILLIMETRES



UTILITY STRUCTURES INC.
61 BONGARD AVE | OTTAWA, ON | K2E 6V2
T: 613.225.6398 F: 613.225.1681 TF: 800.267.6466
www.utilitystructures.com

CONSTRUCTION DETAILS:

- DESIGNED TO CL-625-ONT TRUCK LIVE LOADING AS PER [CSA S6-06](#)
- E-60 BASE AND E-61 PAD ASSEMBLED

CSA 23.4-05

- 35 MPa (5000psi) AT 28 DAYS
- STRIPPING STRENGTH: MIN. 20 MPa(2900psi)
- 5-8% AIR ENTRAINED
- EXPOSURE CLASS: C-1
- REINFORCING: STEEL TO CSA CAN A23.1

PRODUCT DETAILS:

E-60 BASE

- (4) 127mm[5"] POLYLOK PIPESEAL WINDOWS (9 POLYLOKS PER WINDOW)
- CLOSED BOTTOM MANHOLE

E-61 PAD

- PAD OPENING: 686mm[27"]

WEIGHT:

- E-60 BASE: 2,170 kg / 4,774 lbs
- E-61 PAD: 1,130 kg / 2,486 lbs

CUSTOM OPTIONS AVAILABLE:

- CUSTOM WINDOWS, OPENINGS, CABLE RACKS, PULLING EYES & MANHOLE HEIGHT

PRODUCT CODE:	
E-60^C / E-61^W	
5' x 5' ELECTRICAL MANHOLE	
INSIDE DIMENSIONS:	
1.56m(H) X 1300mm x 1300mm	
TOTAL WEIGHT:	
3,300 kg / 7,260 lbs	
REVISION DATE:	JANUARY 24, 2018
REV. #	7